



CAN-BUS Cables: M12 Male Connector With Cable



Specifications

Contacts	5(Male)
Pin layout	
Connector Series	M12
Contact No.	5 Pins
Coding	A
Contacts Material	Brass with gold plated
Nut/Screw Material	Zinc alloy with nickel plated
Connector Insert	TPU
Over-molding	TPU
Jacket Color	RAL4001(Violet RAL4001)
Jacket Material	PUR/PVC
Shielding	Available
IP Rating	IP67/IP69K
Ambient Temperature	-25°C ~ +85°C (flexible installation) , -40°C ~ +85°C (fixed installation)
Contacts Type	Solder version
Rated current	4A
Voltage	60V
Wire gauge/size	1Pair: 24AWG / 1Pair: 22AWG / 2Pairs: 24AWG / 2Pairs: 22AWG
Cable jacket	PUR/PVC
Cable length	Customized Cable Length

Product Features

- 1-Pair or 2-Pair cores of CAN-BUS cables
- M12, A-coded, 5pins
- Single end with customized cable end process
- Suitable for drag chain
- RoHS compliant

Application Fields

- Automotive Industry
- Mechanical Engineering
- Aviation/Aerospace/Marine Engineering
- Automation Control
- Robotics/CNC

Product Advantage

- Used for cost-saving installation of CAN-BUS cable system
- Space-saving solution due to compact dimensions
- Fast and easy to identify error
- Low cost but high productivity
- Standardized interfaces

Cable Construction

- Permanently flexible control cable
- Construction: 1Pair(or 2Pairs)+Shield(AL)+Drain+Braids
- Conductor: Bare copper
- Violet jacket