



Multi-conductor Cable



UL2517 Multi-Conductor Shielded Cable



Product Description

- Tinned, annealed, stranded or solid copper conductor.
- PVC insulation
- PVC jacket
- Tinned or bare copper wire spiral or braid shield
- Rated temperature: 105°C Rated voltage: 300Volts
- Pass UL VW-1&CSA FT1 vertical flame test

Applications

- Tinned, annealed, stranded or solid copper conductor.

Technical Data

UL Style & CSA Type	Cores	Conductor		Insulation Thickness	Nom. Dia	Shield Coverage	Jacket Thickness	Overall Diameter	Conductor Resistance at 20°C
		Gauge	No./OD						
		AWG	No./mm						
UL2517CSA (Stranded)	2C	30	7/0.100	0.41	1.10	≥65	0.76	4.40	381.00
		28	7/0.127	0.41	1.20	≥65	0.76	4.50	239.00
		26	7/0.16	0.43	1.30	≥65	0.76	4.80	150.00
		24	11/0.16	0.41	1.40	≥65	0.76	5.00	94.20
		22	17/0.16	0.43	1.60	≥65	0.76	5.40	59.40
		20	21/0.178	0.41	1.80	≥65	0.76	5.80	36.70
		18	34/0.178	0.41	2.10	≥65	0.76	6.40	23.20
UL2517CSA (Stranded)	3C	30	7/0.100	0.41	1.10	≥65	0.76	4.60	381.00
		28	7/0.127	0.41	1.20	≥65	0.76	4.80	239.00
		26	7/0.16	0.41	1.30	≥65	0.76	5.00	150.00
		24	11/0.16	0.43	1.40	≥65	0.76	5.20	94.20
		22	17/0.16	0.41	1.60	≥65	0.76	5.60	59.40
		20	21/0.178	0.41	1.80	≥65	0.76	6.00	36.70
		18	34/0.178	0.41	2.10	≥65	0.76	6.70	23.20
UL2517CSA (Stranded)	4C	30	7/0.100	0.41	1.10	≥65	0.76	4.80	381.00
		28	7/0.127	0.41	1.20	≥65	0.76	5.00	239.00
		26	7/0.16	0.41	1.30	≥65	0.76	5.30	150.00
		24	11/0.16	0.41	1.40	≥65	0.76	5.60	94.20
		22	17/0.16	0.41	1.60	≥65	0.76	6.00	59.40
		20	21/0.178	0.41	1.80	≥65	0.76	6.50	36.70
UL2517CSA (Stranded)	5C	30	7/0.100	0.41	1.10	≥65	0.76	5.20	381.00
		28	7/0.127	0.41	1.20	≥65	0.76	5.40	239.00
		26	7/0.16	0.41	1.30	≥65	0.76	5.70	150.00
		24	11/0.16	0.41	1.40	≥65	0.76	6.00	94.20
		22	17/0.16	0.41	1.60	≥65	0.76	6.50	59.40
UL2517CSA (Stranded)	6C	30	7/0.100	0.41	1.10	≥65	0.76	5.50	381.00
		28	7/0.127	0.41	1.20	≥65	0.76	5.80	239.00
		26	7/0.16	0.41	1.30	≥65	0.76	6.00	150.00
		24	11/0.16	0.41	1.40	≥65	0.76	6.40	94.20

PVC Jacket cable