


PSG Straight Plug, Cable Collet (Three Keys)

- Connector series: PSG
- Contact: Male
- Locking type: Self-locking
- Orientation type: Straight
- Part No.: PSG.0R.XXX.KLACXXZ
- Mated with: FRG.0R.XXX.KLL



Note: "X" refers to part number definition on page 126


General Information

Ambient temperature:	-20°C ~ + 80°C
Endurance:	≥3000 cycles
Insulator:	PEEK
Connector contacts:	Brass with gold plated
Coupling nut/screw:	Brass with black Cr plated

Housing:	Brass with black Cr plated
Insulator resistance:	≥100MΩ
IP rating:	IP 68
Shielding efficiency:	at 10MHz>75dB/at 1GHz>40dB
Salt spray corrosion test:	>144h

FRG Fixed Socket With Earthing Tag, Front Fasten (Three Keys)

- Connector series: FRG
- Contact: Female
- Locking type: Self-locking
- Orientation type: Straight
- Part No.: FRG.0R.XXX.KLL
- Mated with: PSG.0R.XXX.KLACXXZ



Note: "X" refers to part number definition on page 126

General Information

Ambient temperature:	-20°C ~ + 80°C
Endurance:	≥3000 cycles
Insulator:	PEEK
Connector contacts:	Brass with gold plated
Coupling nut/screw:	Brass with black Cr plated

Housing:	Brass with black Cr plated
Insulator resistance:	≥100MΩ
IP rating:	IP 68
Shielding efficiency:	at 10MHz>75dB/at 1GHz>40dB
Salt spray corrosion test:	>144h

Note: Panel cut-out (page 164)